



DISTRIBUTED BY CLEARLAKE SUPPLY

847.686.2890

FEATURES

- Vulcanized Recycled Rubber
- Suitable for most Rooftop Material
- UV Resistant
- Noise/Vibration Dampening
- Highly Resistant to Freeze/Thaw
- Reflector for High Visibility
- Indented hand hold design/easy transport

APPLICATIONS

- Solar Racking
- HVAC Ducting
- HVAC System Support
- Pipe/Conduit Support
- Cable Tray Systems
- Roof Walkway Systems

INDEPENDENT LAB TESTING

- Ozone Exposure ASTM D1149-18
- Heat Aging ASTM D573-2019
- Hardness (Durometer Shore A) ASTM D2240-2021
- Compressive Strength ASTM D395-2018
- Tensile Testing ASTM D412-2016

FINISHES

- Pre-Galvanized Steel Strut
- Other special order finishes available

MODEL	STRUT LENGTH	STRUT HEIGHT	BLOCK LENGTH	BLOCK HEIGHT	WIDTH	LOAD CAPACITY*	WEIGHT
<input type="checkbox"/> T220V	20 1/4"	13/16"	21 1/4"	5"	5"	3000LBS	6.19 LBS
<input type="checkbox"/> T230V	30.5"	13/16"	31 1/2"	5"	5"	1,500LBS	4.87LBS



*Uniform block load capacity only. Always consult engineer for substrate load capacity.



www.talonroofingproducts.com



info@talonroofingproducts.com

